

Vertical Braiders 140 V SERIES

| Main Models | Horn Gear Size (mm) | Decks Number | Carriers per Deck | Textile Carrier Speed (RPM) | Wire Carrier Speed (RPM) | Capstan Diameter (mm) | Braiding Pitch set-up | Guard | Average Sound Pressure (dBA) |
|--------------------|---------------------|--------------|-------------------|-----------------------------|--------------------------|-----------------------|-----------------------|----------------------|------------------------------|
| 12/1-140 | 140 | 1 | 12 | 78,3 | 66,6 | 450 | Gears | Sound Proofing Cabin | 80 |
| 12/1-140 EC | 140 | 1 | 12 | 78,3 | 66,6 | 400 - 600 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 16/1-140 C | 140 | 1 | 16 | 58,7 | 50 | 450 | Gears | Sound Proofing Cabin | 80 |
| 16/1-140 EC | 140 | 1 | 16 | 58,7 | 50 | 400 - 600 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 24/1-140 C | 140 | 1 | 24 | 39,1 | 33,3 | 600 | Gears | Sound Proofing Cabin | 80 |
| 24/1-140 EC | 140 | 1 | 24 | 39,1 | 33,3 | 500 - 1000 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 32/1-140 EC | 140 | 1 | 32 | 29,3 | 25 | 600 - 1000 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 36/1-140 EC | 140 | 1 | 36 | 26,1 | 22,2 | 600 - 1200 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 48/1-140 EC | 140 | 1 | 48 | 19,5 | 16,6 | 600 - 1200 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |

Vertical Braiders 140 V SERIES

| Main Models | Horn Gear Size (mm) | Decks Number | Carriers per Deck | Textile Carrier Speed (RPM) | Wire Carrier Speed (RPM) | Capstan Diameter (mm) | Braiding Pitch set-up | Guard | Average Sound Pressure (dBA) |
|-----------------------|---------------------|----------------|-------------------|-----------------------------|--------------------------|-----------------------|-----------------------|----------------------|------------------------------|
| 64/1-140 EC | 140 | 1 | 64 | 14,6 | 11,8 | 600 - 1200 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 96/1-140 EC | 140 | 1 | 96 | 9,8 | 7,5 | 600 - 1200 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 12/2-140 C | 140 | 2 (1 motor) | 12 | 78,3+ 78,3 | 66,6 + 66,6 | Rollers dia 100 mm | Gears | Sound Proofing Cabin | 80 |
| 16/2-140 C | 140 | 2 (1 motor) | 16 | 58,7 + 58,7 | 50,0 + 50,0 | Rollers dia 100 mm | Gears | Sound Proofing Cabin | 80 |
| 12/2-140 EC | 140 | 2 (1 motor) | 12 | 78,3+ 78,3 | 66,6 | Rollers dia 100 mm | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 16/2-140 EC | 140 | 2 (1 motor) | 16 | 58,7 + 58,7 | 50 | Rollers dia 100 mm | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 24+24/140 V/EC | 140 | 1+1 in line | 24 | 39,1 | 33,3 | 500 - 1000 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 36+36/140 V/EC | 140 | 1+1 in line | 36 | 26,1 | 22,2 | 800 - 1000 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |
| 64+64/140 V/EC | 140 | 1+1 in line | 64 | 14,6 | 11,8 | 800 - 1000 | Electronic SIAX 110 | Sound Proofing Cabin | 80 |