

**Horizontal Braiders 190 H SERIES**

Carrier type	Application	Thread Passage and Exit	Bobbin Dimensions fl.Ø - trav. (mm)	Bobbin Capacity (cm <sup>3</sup> )	Tension Range (Kg)		Bobbin Dimensions fl.Ø - trav. (inch)	Bobbin Capacity (inch <sup>3</sup> )	Tension Range (libbre)		Max. Horn Gear Speed (RPM)
					Min	Max			Min	Max	
<b>190 M</b>	Steel Wire Brassed	Rollers T. Carbide Eyelet	86 x 201	1076	5	20	3,30 x 8,00	66	10	40	180
<b>190 M/S</b>	Steel Wire Inox	Rollers T. Carbide Eyelet	86 x 201	1076	5	20	3,30 x 8,00	66	10	40	180
<b>190 M/SR</b>	Steel Wire Brassed / Inox	Rollers and Swivel Heads	86 x 201	1076	5	20	3,30 x 8,00	66	10	40	180
<b>190 M/DT</b>	Textile Yarns	Double Trade Rollers + T. Carbide Eyelet	86 x 201	1076	3	10	3,30 x 8,00	66	6	22	180
<b>190 T</b>	Textile Yarns	Rollers + Ceramics	90 x 300	1700	1	5	3,30 x 8,00	66	6	22	180
<b>190 T/G</b>	Textile Yarns	Rollers + Ceramics	90 x 380	1800	1	5	3,54 x 1,80	178	2	10	180