

Automatic Winding Machines BTA SERIES

	BTA 4/90	BTA 2/300 ME	BTA 2/300 M/ ESP	BTA 2/300
Number of Spindles	4	2	2	2
Bobbin Rotation Speed	0 - 6000 giri/1'	0 - 6000 giri/1'	0 - 6000 giri/1'	0 - 3000 giri/1'
Constant Linear Speed of the Wire/Yarn	0 - 1000 ml/1'	0 - 1000 ml/1'	0 - 1000 ml/1'	Non Disponibile
Flange Diameter Min - Max	40 - 90 mm	40 - 90 mm	40 - 100 mm	40 - 100 mm
Internal Length Min - Max	100 - 300 mm	50 - 200 mm	50 - 300 mm	80 - 300 mm
Material to Wind	Natural and Synthetic Yarns	Low Resistance Steel, Aluminium and Copper Wires	Natural and synthetic yarns	Natural and synthetic yarns
Yarn/Wire guide	Servo Controlled A.C. Motors	Brushless Motors	Brushless motors	Adjustable mechanical traverse unit
Yarn/Wire Binding	Not Available	Adhesive Label at Start or End of Bobbin Selectable	Adhesive Label at Start or End of Bobbin Selectable	Not Available
Label Adaptation to Bobbin Diameter	Not Available	Automatic	Automatic	Not Available
Yarn/Wire Linear Speed	Constant or Variable Selectable from Recipes	Constant or Variable Selectable from Recipes	Constant or Variable Selectable from Recipes	Variable
Control and Management	N.C. with Recipes Memorisation	N.C. with Recipes Memorisation	N.C. with Recipes Memorisation	Electro-pneumatic
Full Bobbin Collection	Drawer Guide	Guide with Automatic Displacement	Guide with Automatic Displacement	Drawer