

Reel Take-Up Stands Machines

Main Models	Bobbin Dimension Min. - Max. Fl. Dia. x Int. Width (mm)	Capacity Max. (Kg)	Winding Speed Max. (ml/1 min.)	Tension Min. - Max. (Kg)	Lifting
CAV 368	400 x 200 800 x 400	250	5	0,5 - 5	Manual Lever
CAV 800	800 x 400	250	5	0,5 - 5	Manual Lever
CAP 800	600 x 300 800 x 400	300	30	1 - 5	Manual Pump
CAV 581	500 x 300 1000 x 650	250	5	0,5 - 5	Manual Lever
CAV 1000	1000 x 650	250	5	0,5 - 5	Manual Lever
CAV 1000 P	1000 x 650	1000	20	0,5 - 15	Manually Controlled Hydraulic Pump
CAV 1000 CMP	600 x 400 1000 x 650	1000	120	0,5 - 20	Electric Motor
CAV 1200 P	1200 x 650	1000	20	0,5 - 15	Manually Controlled Hydraulic Pump
CAV 1200 CMP	800 x 500 1200 x 650	1000	120	0,5 - 20	Electric Motor

Reel Take-Up Stands Machines

Main Models	Bobbin Dimension Min. - Max. Fl. Dia. x Int. Width (mm)	Capacity Max. (Kg)	Winding Speed Max. (ml/1 min.)	Tension Min. - Max. (Kg)	Lifting
CAV 1500 P	1000 x 650	1000	30	0,5 - 15	Manually Controlled Hydraulic Pump
CAV 1500 CMP	1000 x 650 1500 x 800	1000	120	0,5 - 20	Electric Motor
CAV 1800 CMP	1800 x 1000	2000	70	1 - 30	Electric Motor
CAV 2000	2000 x 1140	5000	70	3 - 50	Hydraulic
CAV 2500	2500 x 1200	6000	70	3 - 70	Hydraulic
CAV 2800	2800 x 1800	6000	70	3 - 70	Hydraulic
CASM 63/200	630 x 400 2000 x 1140	5000	120	3 - 70	Electric Motor
CASM 10/250	1000 x 650 2500 x 1200	6000	120	3 - 70	Electric Motor
CAV 4000	4000 x 3800	40000	100	10 - 400	Electric Motor